



## CIRCULAR SAW BLADES



# HSS-METAL CIRCULAR SAW BLADES



Manufacturer	Dimensions	No. of teeth and tooth profile					HSS	HSS dampened
<b>Baier</b> with 4 offset keyways	175 x 2.0 x 32	A 180 AW	D 5 100 C	E 6 80 C		•		
		E 12 48 C			•			
		B 220 AW	D 2.5 200 B		•			
	250 x 2.0 x 32	C 360 AW				•		
		A 250 AW	D 5 160 C	E 6 128 C		•		
		E 12 64 C				•		
B 320 AW		D 2.5 300 B			•			
C 500 A				•				
<b>Eisele</b> 22/ = without NL 32/ = 2/8/45 40/ = 2/8/55	210 x 2.0 x 32	210 BW	160 BW	120 C	80 C		•	
	210 x 2.0 x 40	210 BW	160 BW	120 C	80 C		•	
	225 x 2.0 x 32	220 BW	180 BW	120 C	90 C		•	
	225 x 2.0 x 40	220 BW	180 BW	120 C	90 C		•	
	250 x 2.0 x 40	200 BW	128 C	100 C			•	
	250 x 2.5 x 40	200 BW	128 C	100 C			•	
	275 x 2.0 x 40	280 BW	220 BW	140 C	110 C		•	
	275 x 2.5 x 40	280 BW	220 BW	140 C	110 C		•	
	300 x 2.5 x 40	220 BW	160 C	120 C			•	
	315 x 2.5 x 40	250 BW	160 C	120 C	100 C	80 C	•	
	315 x 3.0 x 40	250 BW	160 C	120 C	100 C	80 C	•	
	350 x 3.0 x 40	280 BW	180 C	140 C	110 C	90 C	•	
	400 x 3.0 x 40	310 BW	200 C	160 C	128 C	100 C	•	
	400 x 3.5 x 40	310 BW	200 C	160 C	128 C	100 C	•	
	<b>Kaltenbach</b> 32/ = without NL 50/ = 4/15/80	220 x 2.0 x 32	100 BW	80 BW	64 BW			•
250 x 2.0 x 32		100 BW	80 BW	64 BW			•	
350 x 2.5 x 50		220 BW	160 C	120 C	100 C	80 C	•	
350 x 3.0 x 50		220 BW	160 C	120 C	100 C	80 C	•	
370 x 3.0 x 50		220 BW	160 C	120 C	100 C	80 C	•	
400 x 3.0 x 50		180 C	100 C	80 C			•	
400 x 3.5 x 50		180 C	100 C	80 C			•	
<b>Metora</b> 250/ = 2/9/56 275/ = 2/11/80 350/ = 2/11/80	250 x 2.0 x 32	200 BW	128 C	100 C			•	
	275 x 2.0 x 32	220 BW	140 C	110 C			•	
	275 x 2.5 x 32	220 BW	140 C	110 C			•	
	300 x 2.5 x 32	220 BW	160 C	120 C			•	
	350 x 2.5 x 32	200 BW	120 C				•	
<b>Trennjäger</b> 32/ = 2/9/50 40/ = 4/11/63 50/ = 4/14/85	250 x 2.0 x 32	196 BW	120 C	72 C			•	
	250 x 2.5 x 32	196 BW	120 C	72 C			•	
	250 x 2.5 x 40	196 BW	120 C	72 C			•	
	275 x 2.5 x 40	220 BW	120 C	96 C			•	
	300 x 2.5 x 32	240 BW	156 C	94 C			•	
	315 x 3.0 x 50	250 BW	138 C	112 C	84 C		•	
350 x 3.2 x 50	220 BW	160 C	128 C	96 C		•		

# HSS-SEGMENTED CIRCULAR SAW BLADES



The hole and secondary hole can be supplied to suit any circular saw machine.

HSS metal circular saw blades are resharpened by sub-contractors and charged according to cost.

Other dimensions available on request.

Diameter mm	Cutting width mm	Number of segments
210	3.0	10
250	3.0	12
275	3.0	12
300	3.6	14
315	3.6	14
340	3.6	16
360	3.6	16
370	3.6	16
400	4.0	16
425	4.0	18
460	5.0	18
500	5.6	20
560	5.0	18
570	5.7	18
630	5.0	20
630	6.0	20
660	5.0	20
660	6.0	20
710	6.3	24
760	6.7	24
800	7.0	24
810	6.8	24
920	7.8	30
970	7.8	30
1020	8.3	30
1120	8.3	36
1250	8.9	32
1320	9.3	36
1430	9.5	36